



The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#)

Tools: Add to Work File: Create new Work File ☐

View: INPADOC | Jump to: [Top](#)

☐ Email this to a friend

Title: **JP5154816A2: PRODUCTION OF FIBER REINFORCED CEMENT SLAB**

Country: **JP Japan**

Kind: **A**

Inventor: **NOZAKI AKITOSHI;
KOMATSU KAZUYUKI;**

Assignee: **KUBOTA CORP**
[News, Profiles, Stocks and More about this company](#)

Published / Filed: **1993-06-22 / 1991-12-03**

Application Number: **JP1991000348234**

IPC Code: **B28B 3/12; B28B 1/30; B28B 1/52;**

Priority Number: **1991-12-03 JP1991000348234**


Abstract: **PURPOSE:** To obtain a fiber reinforced cement slab having the same strength as flow-on molding at the speed corresponding to that of a dry method by a method wherein a cement slurry is supplied to the upper surface of a water permeable molding belt to be formed into a slurry layer by a compression roller while moisture is sucked from the rear surface of the belt and this operation is repeated in the same way to laminate respective layers.

CONSTITUTION: A cement slurry may be same to that used in a flow-on manufacturing method. First - fourth flow boxes 10-40 are provided on the front side of a water permeable molding belt and dehydrating suction boxes 11-41 are provided to the rear of the belt corresponding to the flow boxes. The cement slurry S is supplied to the belt in a laminar state from the first flow box 10 and sucked and dehydrated from the suction box 11 while compressed by a compression roll 51 having a polyethylene layer provided on the surface thereof. This operation is repeated using the second - fourth flow boxes 20-40 to laminate respective formed layers. Compressed air is sent to the rear air box 54 of the molding belt at the terminal B7 thereof to release a laminated sheet which is, in turn, sent to a curing process.

COPYRIGHT: (C)1993,JPO&Japio

Family: **None**

Other Abstract Info: **None**



[View Image](#)

1 page

